

DATASHEET

+39310



RCD + DIST ENCL (2x8+3x16) 64md D125 FM

Dimensions WxHxD (mm)	400x750x125
EAN	5600307030769
Rows x Modules	2x8+3x16
Application	Flush Mounted (FM)
No. Frames for DIN rail	5
Locking System	2 Flat plastic handle lock
Color	White - RAL 9010
Tariff Code	85381000
Gross Weight (Kg)	6.75
Volume (m³)	0.051

Materials

Enclosure	Plastic - PSHI
Frame and door	White lacquered aluminium
Chassis	Aluminium
BUSBARS	PA support and brass busbar

Protection and Security

Insulation Class	Class II Insulation
IP Protection Degree	54
IK Protection Degree	07
GWT	850°C
Static Load	200kg/m ³
Installation Temperature	Mín: -5°C Máx: 40°C

Electrical Features

In	125A
Ue	230V/400V~
Ui	690V
Pde - 30K	51W
Frequency	50Hz

Included Accessories

Neutral N° Busbars	5x(1x25mm ² + 9x16mm ²)
Earth N° Busbars	1x(1x25mm ² + 9x16mm ²) 2x(12x10mm ² + 11x16mm ²)
Blanking Plates	2x12md
Circuit Marking Labels	Yes

Standardizing Documentation

Standards	EN 62208
Directive	2014/35/UE
Regulations	RTIEBT

Nota:The image may not correspond to the product code shown. Please refer to the technical specifications.