

DATASHEET

+41640



RCD + DIST ENCL (2x16+5x24) 152md D125 SM

Dimensions	550x1000x125
WxHxD (mm)	
EAN	5600307030899
Rows x Modules	2x16+5x24
Application	Surface Mounted (SM)
No. Frames for DIN rail	7
Locking System	2 Flat plastic handle lock
Color	White - RAL 9010
Tariff Code	85381000
Gross Weight (Kg)	16.95
Volume (m³)	0.103

Observations FPE - Product not available for immediate delivery, manufactured to order and subject to longer delivery times and/or minimum quantities.

Materials

Enclosure	Plastic - PSHI
Frame and door	White lacquered aluminium
Chassis	Aluminium
BUSBARS	PA support and brass busbar

Protection and Security

Insulation Class	Class II Insulation
IP Protection Degree	54
IK Protection Degree	09
GWT	850°C
Static Load	200kg/m ³
Mechanical Reinforcement	Sim
Installation Temperature	Mín: -5°C Máx: 40°C

Electrical Features

In	125A
Ue	230V/400V~
Ui	690V
Pde - 30K	116W
Frequency	50Hz

Included Accessories

Neutral	6x(1x25mm ² + 9x16mm ²) 2x(12x10mm ² + 11x16mm ²)
Nº Busbars	
Earth	3x(1x25mm ² + 9x16mm ²) 3x(12x10mm ² + 11x16mm ²)
Nº Busbars	

Blanking Plates	3x12md
Circuit Marking Labels	Yes
Fixing Kit	Sim

Standardizing Documentation

Standards	EN 62208
Directive	2014/35/UE
Regulations	RTIEBT

Nota:The image may not correspond to the product code shown. Please refer to the technical specifications.