

## DATASHEET

+44215

### JUNCTION ENCL 2 OUT 95/16 D125 SM



<b>Dimensions WxHxD (mm)</b>	475x375x125
<b>EAN</b>	5600307030585
<b>Application</b>	Surface Mounted (SM)
<b>Locking System</b>	Triangular plastic cam lock + key
<b>Color</b>	White - RAL 9010
<b>Tariff Code</b>	85381000
<b>Gross Weight (Kg)</b>	4.25
<b>Volume (m³)</b>	0.032

### Materials

<b>Enclosure</b>	Plastic - PSHI
<b>Frame and door</b>	White lacquered aluminium

### Protection and Security

<b>Insulation Class</b>	Class II Insulation
<b>IP Protection Degree</b>	54
<b>IK Protection Degree</b>	07
<b>GWT</b>	850°C
<b>Static Load</b>	200kg/m³
<b>Installation Temperature</b>	Mín: -5°C Máx: 40°C

### Electrical Features

<b>Ue</b>	230V/400V~
<b>Ui</b>	690V
<b>Pde - 30K</b>	47W
<b>Frequency</b>	50Hz

### Standardizing Documentation

<b>Standards</b>	EN 62208
<b>Directive</b>	2014/35/UE
<b>Regulations</b>	RTIEBT

**Nota:**The image may not correspond to the product code shown. Please refer to the technical specifications.