

**DATASHEET**
**00145448**
**DISTRIBUTION ENCL (2x24) 48md D200 SM**


<b>Dimensions WxHxD (mm)</b>	550x375x200
<b>Locking System</b>	Flat plastic handle lock
<b>Color</b>	Grey - RAL 7035

**Observations** Boxes manufactured with metal coating, increasing Mechanical Resistance Reinforcement, and painted gray.

**Materials**

<b>Enclosure</b>	Plastic - PSHI
<b>Frame and door</b>	Aluminium

**Protection and Security**

<b>Insulation Class</b>	Class II Insulation
<b>IP Protection Degree</b>	43
<b>IK Protection Degree</b>	09
<b>GWT</b>	850°C
<b>Static Load</b>	200kg/m <sup>3</sup>
<b>Installation Temperature</b>	Mín: -5°C Máx: 40°C

**Electrical Features**

<b>Ue</b>	230V/400V~
<b>Ui</b>	500V
<b>degree of pollution</b>	3
<b>Frequency</b>	50Hz

**Standardizing Documentation**

<b>Standards</b>	EN 62208
<b>Directive</b>	2014/35/EU
<b>Regulations</b>	RTIEBT

**Nota:**The image may not correspond to the product code shown. Please refer to the technical specifications.